



Cannondale Demystified – Which C-BEAR bottom bracket??

	PF30A	BB30A	BB30	PF30
BB shell ID (mm)	46	42	42	46
BB shell width	73	73	68	68

Cannondale	CAAD12	CAAD10
Slice 2015 onwards	Slate	
Supersix 2016 onwards Super X 2017		SuperSix SuperSix
SystemSix 2019	Synapse 2014 onwards	

24mm crank				
Shimano/Race Face/FSA	PF30A -24 R or AC	BB30A- 24 R or AC	BB30-24 R or AC	PF30-24 R or AC
SRAM GXP	PF30A GXP R or AC	BB30A GXP R or AC	BB30-GXP R or AC	PF30-GXP R or AC
25 mm crank				
Campa UT			BB30-cam-ut R only	PF30-cam-ut R only
30mm crank				
Hollowgram	PF30A R or AC	PF42-30* R or AC	PF42-30* R or AC	PF30 R or AC
ROTOR 3D+, Aldhu, 3DF, Rex1, Rex2	PF30A 86	BB30A 86	BB30-86	PF30-86
Sram Quarq DZero	R only	R only available	R or AC	R or AC
Easton EC90				
BB30 SRAM/FSA			PF42-30* R or AC	PF30 R or AC
FSA EVO386			BB30-386 R or AC	PF30-386 R or AC

PF42-30* or BB30 bearing direct mount



ceramic bearing type

R = Road ceramic bearing (black seal)

AC = All conditions (red seal)

C-BEAR offers 2 options since beginning of operation in 2007 #leadnofollow

R for least friction resistance

AC with different spec and design for better protection against external elements such as moisture and debris, suitable for wet humid weather condition.